

TriPosit®
New Construction With Wall Cap
TRI 501

Diagram

Updated: 11/06




*Quality You Can Trust Since 1886...
From North America's Largest Roofing Manufacturer™*

INTERMITTENT FASTENING KEY

54" WITH BONDING ADHESIVE

18" DRY

NAIL COPING
12" O.C.



BACK SIDE

COPING CAP

EVERGUARD® BONDING ADHESIVE

EVERGUARD® REINFORCED MEMBRANE

DRILL-TEC™ PLATES & SCREWS
12" O.C.

HEAT WELDED LAP

EVERGUARD® REINFORCED FLEECEBACK MEMBRANE


8" min.

ENERGYGUARD™ ROOF INSULATION

ROOF DECK/SUBSTRATE

GAF BUR ASSEMBLY

ALTERNATE BASE
REFER TO 307



NOTE:

1. FOR INSULATION THICKNESS GREATER THAN 8" CONTACT GAFMC CONTRACTOR SERVICES FOR ALTERNATE MEMBRANE ATTACHMENT REQUIREMENTS.
2. APPLY EVERGUARD® TPO CUT EDGE SEALANT TO ALL CUT REINFORCED TPO EDGES (REFER TO DETAIL MA/FA/BA 115).



NEW CONSTRUCTION WITH WALL CAP

DRAWING #

TRI 501

SCALE

N.T.S.

ISSUE/ REVISION DATE

11-01-06