

Freedom™
Wall Flashing
With Coated Metal Edge
FD 304



Diagram

Updated: 11/06



*Quality You Can Trust Since 1886...
From North America's Largest Roofing Manufacturer™*

RS MAX 10 YR WARRANTY



NAIL 12" O.C. W/ RING SHANK NAIL

24 GA. CONTINUOUS CLIP
FASTENED 12" O.C. WITH
DRILL-TEC™ FASTENERS

EVERGUARD® COATED METAL

GALV. METAL NAILED 4" O.C.
STAGGERED OR DRILL-TEC
SCREWS 12" O.C.

HEAT WELDED LAP

GAF TPO COVER TAPE OR 8"
FREEDOM STRIPS

HEAT WELDED LAP

EVERGUARD® FREEDOM
FLASHING

DRILL-TEC™ PLATES & SCREWS
12" O.C.

RAPID SEAM LAP

EVERGUARD® FREEDOM
MEMBRANE


ENERGYGUARD™ ROOF
INSULATION

ROOF DECK/SUBSTRATE

NOTE:

1. TO MAKE A SEAM ON RS WITHOUT RS PRESENT, YOU MUST USE GAF CLEANER AS WELL AS GAF PRIMER TO PREP THE AREA.
2. FOR INSULATION THICKNESS GREATER THAN 8", CONTACT GAFMC CONTRACTOR SERVICES FOR ALTERNATE MEMBRANE ATTACHMENT REQUIREMENTS.
3. APPLY EVERGUARD® TPO CUT EDGE SEALANT TO ALL RAPID SEAM EDGES (REFER TO DETAIL FD 115).

ALTERNATE BASE
REFER TO 307



**WALL FLASHING WITH COATED METAL
EDGE**

FREEDOM RS ONLY

DRAWING #
FD 304

SCALE	ISSUE/ REVISION DATE
N.T.S.	11-01-06