


Three (3) Ply SBS Hot Mopped System Lightweight Insulating Concrete

Diagram



*Quality You Can Trust Since 1886...
From North America's Largest Roofing Manufacturer™*

THREE (3) PLY SBS HOT MOPPED SYSTEM LIGHTWEIGHT INSULATING CONCRETE



GENERAL

Safety: Refer to Section 1.06.
DO NOT BEGIN INSTALLATION
UNTIL THIS INFORMATION IS READ,
UNDERSTOOD AND IMPLEMENTED.

MATERIALS

Material Requirements per 100 sq. ft.:
Asphalt (per ply)25 lbs. (1.22 kg/m²)
Base Sheet1 ply
Interply2 plies
Membrane1 ply

15 YEAR DIAMOND PLEDGE AND SYSTEM PLEDGE GUARANTEES

	BOTTOM SHEET			
<u>SPEC#</u>	<u>ATTACHMENT</u>	<u>BASE SHEET</u>	<u>INTERPLY</u>	<u>CAP</u>
N-2-1-MGP	FASTENER	STRATAVENT® NAILABLE	FLEXPLY™ 6	MOP GRANULE PLUS
N-2-1-MGPFR	FASTENER	STRATAVENT NAILABLE	FLEXPLY 6	MOP FR

Hot Mopped Systems