

Exterior Masonry and Stucco Wall Restoration

Information Sheet

Updated: 1/07



*Quality You Can Trust Since 1886...
From North America's Largest Roofing Manufacturer™*

Exterior Masonry & Stucco Wall Restoration

Original Application

- Traditional Installations: Exterior masonry and stucco walls.
- Typical Property: Large low-rise buildings, warehouses and publicly owned buildings.
- Reason for Installation: Waterproof and protect vertical masonry surfaces, including parapet walls.

System Advantage

Seam-Free™ protection for walls; provides superior water resistance, great looks, and the long-lasting protection of an elastomeric membrane.

Features

- Protection: Waterproof and protect walls, decorative.
- Durable: Designed to withstand harsh climates.

Guarantee Eligibility

- Eligible for 10 Year Emerald Pledge™ NDL Warranty*
- Can be part of the 20 Year Diamond Pledge™ NDL Guarantee*

TOPCOAT® System Advantages

- Reflectivity: High reflectivity can mean substantial energy savings by reducing interior building temperatures.
- Guarantees backed by GAFMC, North America's largest roofing materials manufacturer.*
- Diamond Pledge™ NDL Guarantee.*
- Emerald Pledge™ NDL Warranty.*
- High Solids: Liquid applied membrane with 60 ± 2% solids; average membrane thickness is 24-30 dry mils when applied at 2 gallons per square.
- Performance: Elastomeric properties provide a stronger resistance to discoloration and fading while helping to resist blistering, flaking and peeling.
- Extra Protection: Helps to prevent weather infiltration while providing a breathable membrane.

Quick Spec

- Step 1) Pressure wash walls.
- Step 2) Treat all wall penetrations, splits, drains and scuppers with TOPESTER Fabric embedded into TOPCOAT® Flashing Grade.
- Step 3) Treat all splits and cracks with TOPCOAT® Flashing Grade and TOPESTER Fabric.
- Step 4) Spray apply base coat of WallCote™ Wall Coating at 1 gallon per square, and immediately back roll into surface.
- Step 5) Spray apply finish coat of WallCote™ Wall Coating at 1 gallon per square.

Be sure to consult the TOPCOAT® Restoration Solutions Specifications Manual for more detailed information.

*See warranty and guarantee for complete coverage and restrictions.

Quick Specs
and Tips

