

TopCoat® Recommended Equipment

Information Sheet

Updated: 1/07



*Quality You Can Trust Since 1886...
From North America's Largest Roofing Manufacturer™*

TOPCOAT® RECOMMENDED EQUIPMENT

The GAFMC Contractor Services Department recommends that the following tools and equipment be on site and available for the preparation and installation of TOPCOAT® Restoration, Repair and/or Maintenance Systems:

- Adequate water source for pressure washing and clean-up
- Adequate source of electrical power
- Wire brush for removing rust
- Utility knives
- Metal snips
- Reciprocating saw
- Drill or screw gun for tightening fasteners (or T-bar with hex fitting to match fastener size)
- Polyurethane foam or closed-cell foam strips to fill excessive voids in ridge vents, duct work, etc., before TOPCOAT® Flashing Grade and TOPESTER Fabric are applied
- Thick-bristle brushes (2"-4") to apply various TOPCOAT® products
- Low-nap rollers to apply various TOPCOAT® products
- Caulking guns for application of TOPCOAT® Flashing Grade and Fastener Grade in cartridges
- EverTite™ self-drilling stitching screws to properly secure seams, ridge cap, and penetrations
- Pressure washer with minimum working pressure of 3,000 psi equipped with roto-spray tip
- Airless spray system with a minimum working pressure of 2,000 psi/3,000 psi (remove filters) and reversible spray tips for TOPCOAT® product application
- Leister Heat Gun or soldering pencil with pencil tip to make holes in TOPESTER Fabric around fasteners that are present when three coursing
- Rags

For application questions, please contact GAFMC Contractor Services at 1-800-766-3411